





## **Purpose**

LiNX is a technologically advanced seamless system with revolutionary wireless programming tools designed to perform on any power wheelchair application. From simple drive-only systems to highly configurable and customisable complex rehab systems, LiNX has the flexibility to meet your product portfolio needs with one system. This product overview is created to help you understand and visualise the different modules and their primary feature sets.

PRODUCT CODE	DESCRIPTION	PAGE NO.
POWER MODULES		
DLX-PM40-A DLX-PM50-A DLX-PM60-C DLX-PM75-C DLX-PM120-C DLX-PM60AL-C DLX-PM75AL-C DLX-PM120AL-C	Linx 40 A Power Module Linx 50 A Power Module Linx 60 A Power Module Linx 75 A Power Module Linx 120 A Power Module Linx 60 A PM + ACT + LIGHTS LINX 75 A PM + ACT + LIGHTS LINX 120 A PM + ACT + LIGHTS	2 2 2 2 2 2 2 2
REMOTES		
DLX-REM050-A DLX-REM060-A DLX-REM110-A DLX-REM210-A DLX-REM211-A DLX-REM215-A DLX-REM216-A DLX-REM400-B DLX-REM500-A DLX-ACU200-A DLX-CR400-A	LINX LOW PROFILE REMOTE LINX TRADITIONAL REMOTE ENH LINX REMOTE + LTD SEAT LINX REMOTE + FULL SEAT LINX REM + LIGHTS + LTD SEAT LINX REM + LIGHTS + FULL SEAT LINX TOUCHSCREEN REMOTE LINX SPECIALITY DISPLAY LINX ATTENDANT DUAL REMOTE LINX COMPACT REMOTE	3 3 4 4 4 5 5 5 6 6
ACTUATOR MODULE	es e	
DLX-ACT200-A DLX-ACT400-A DLX-TILT200-A	LINX 2 CHANNEL ACTUATOR MODULE LINX 4 CHANNEL ACTUATOR MODULE LINX ANGLE SENSOR	7 7 7
SECONDARY MODULES		
DLX-IN200-A	LINX 10 WAY SWITCH MODULE LINX GYRO MODULE LINX INPUT MODULE LINX DRIVE INPUT MODULE LINX OUTPUT MODULE LINX USB CHARGER	8 8 8 9 9
ACCESSORIES		
DLX-TPI500-A LINX THIRD PARTY INTERFACE LINX ACCESS PROGRAMMING & DIAGNOSTIC TOOLS LINX CABLES		10 10 10



#### FEATURE ICONS

Product has Bluetooth® connectivity



#### **Linx LE Series Power Modules**

#### DLX-PM40-A, DLX-PM50-A

- 40 and 50 A
- Programmable boost current
- 1 x Bus socket
- Dynamic Load Compensation (the same table based Load Compensation value applied to both motors)
- Works with REM50, 60 & 110 remote modules





#### **LiNX 100 Series Power Modules**

DLX-PM60-C, DLX-PM75-C, DLX-PM120-C

Includes all DLX-PM40 & 50 features plus:

- 60 A, 75 A and 120 A
- 2 x Bus sockets
- Adaptive Load Compensation when used with REM110 or higher level remote (learns actual value separately for L and R motors)
- Real-time clock
- 2 x general purpose control inputs\* (CI) for inhibit, function change and drive slow down
- 1 x general purpose control input/output
- Gyro module compatible
- On-board charger inputs
- Statistics recorder

### **LiNX 200 Series Power Modules**

DLX-PM60AL-C, DLX-PM75AL-C, DLX-PM120AL-C

Includes all DLX-PM40 & 50 features plus:

- 60, 75 & 120 A
- 2 x actuator outputs (independent of each other and motor drive)
- Lighting outputs (24V /12V) (position lights and indicators)
- 2 x Bus sockets
- Adaptive Load Compensation when used with REM110 or higher level remote (learns actual value separately for L and R motors)
- Real-time clock
- 3 x general purpose control inputs\* (CI) for inhibit, function change and drive slow down
- 1 x general purpose control input/output
- Gyro module compatible
- On-board charger inputs
- Statistics recorder



<sup>\*</sup> Control inputs include support for slow down/lock out and max angle signals as well as switch inputs.





#### **LiNX Low Profile Remote Module**

#### DLX-REM050-A

- On/off
- Speed dial
- Horn
- Battery gauge
- Hand rest area
- Dynamic Load Compensation

## **LiNX Traditional Remote Module**

#### DLX-REM060-A

- On/off
- Speed dial
- Horn
- Battery gauge
- Dynamic Load Compensation





# LiNX Enhanced Traditional Remote Module

#### DLX-REM110-A

- On/off
- Speed dial
- Horn
- Battery gauge
- Adaptive Load Compensation





## **LiNX Remote Module - Seating**

#### DLX-REM210-A

- On/off
- Speed dial
- Horn
- Battery gauge
- LED icon-based menu
- Two rocker switches for access to 3 x drives and up to 2 actuators
- Adaptive Load Compensation
- No secondary inputs allowed
- Compatible with DLX-ACU200-A

#### DLX-REM211-A

- On/off
- Speed dial
- Horn
- Battery gauge
- LED icon-based menu
- Two rocker switches for access to 3 x drive functions and up to 6 actuators
- Adaptive Load Compensation
- Fully expandable with other LiNX modules (excludes DLX-IN500-A)





# LiNX Remote Module - Lights & Seating

#### DLX-REM215-A

- On/off
- Speed dial
- Horn
- Battery gauge
- LED icon-based menu
- Two rocker switches for access to 3 x drives and up to 2 actuators
- Adaptive Load Compensation
- Lighting control (position lights and indicators)
- No secondary inputs allowed
- Compatible with DLX-ACU200-A





#### DLX-REM216-A

- On/off
- Speed dial
- Horn
- Battery gauge
- LED icon-based menu
- Two rocker switches for access to 3 x drive functions and up to 6 actuators
- Adaptive Load Compensation
- Lighting control (position lights and indicators)
- Fully expandable with other LiNX modules (excludes DLX-IN500-A)

### **LiNX Touchscreen Remote**

#### DLX-REM400-B

- Highly configurable touch interface with swipe/tap and left/right hand interaction modes
- Very flexible user menu (mix'n'match functions and profiles)
- Adjustable brightness 3.5" colour LCD screen
- 2 x multi-purpose buttons
- 2 x 3.5mm stereo jack sockets for switches and on/off
- Field upgradeable toggle switches (DLX-SW400TGL-A)
- Audible cues for speciality control use
- · List and grid menu navigation and scanning
- Bluetooth connectivity functions
- High quality CNC alloy construction
- Speedo and Odometer





# **LiNX Speciality Display**

#### DLX-REM500-A

- Designed specifically for speciality control use
- Pair with any LiNX joystick remote, or 3rd party speciality inputs
- Highly configurable touch interface with swipe/ tap & left/right hand interaction modes
- Adjustable brightness 3.5" colour LCD screen
- 2 x multi-purpose buttons
- 2 x 3.5mm stereo jack sockets for switches and on/off
- Audible cues for speciality control use
- · List and grid menu navigation and scanning
- · Bluetooth connectivity functions
- High quality CNC alloy construction
- Speedo and Odometer





#### **LiNX Attendant Dual Remote**

#### DLX-ACU200-A

- Compact dual control remote for attendant or carer
- Can be added to any LiNX system (excludes LE)
- Flexible who's-in-charge options
- On/off and function buttons to access drive and seating
- 10 x LED display

## **LiNX Compact Remote**

DLX-CR400-A and DLX-CR400LF-A

- Compact remote for users with small range of movement or who want centre-mounted remote
- Pairs with either the REM400 or REM500
- On/off and function buttons for full access to drive, seating and connectivity functions
- Low-force joystick option has a joystick deflection force of <112 grams (CR400LF)</li>
- 10 x LED display

NOTE: Standard LiNX remotes have joystick deflection forces of <163 grams.







\* Control inputs include support for slow down/lock out and max angle signals as well as switch inputs.

#### **LiNX 2 Channel Actuator Module**

#### DLX-ACT200-A

- On-board angle sensor
- Status LED
- Refined actuator control
- Per channel control of actuator current (no shared H-bridges)
- Connectors:
  - 2 x bus ports
  - 2 x actuator ports
  - 4 x control inputs\* (CI) pins and 2 ground pins

#### **LiNX 4 Channel Actuator Module**

#### DLX-ACT400-A

- On-board angle sensor
- Status LED
- Refined actuator control
- Per channel control of actuator current no shared H-bridges)
- Connectors:
  - 2 x bus ports
  - 4 x actuator ports
  - 4 x control inputs\* (CI) pins and 2 ground pins





## **LiNX Angle Sensor**

# DLX-TILT200-A / DLX-TILT201-A / DLX-TILT202-A

- Wired angle sensor for seat position and stability control
- Small dimensions for easy mounting on seat components
- Set multiple angles to trigger different actions

NOTE: TILT200 variant is unterminated, TILT201 has 6 way Mini Fit Jr connector, TILT202 has 2 way Mini Fit Jr connector



## **LiNX 10-Way Switch Module**

DLX-SW10T-A, DLX-SW10-A

- Direct access for 5-10 functions
- Keypad able to be labelled by the OEM
- Wired unit (DLX-SW10T-A is terminated, DLX-SW10-A is unterminated)

## **LiNX Gyro Module**

#### DLX-GYR100-A

- Can be added to any LiNX power module (except LiNX LE Series Power Modules)
- Enhanced tracking and drive stability
- Improved straight line driving on cambers and over obstacles such as thick carpet





## **LiNX Input Module**

#### DLX-IN200-A

- Adds external on/off and non-drive switch functionality to 100 and 200 level systems
- DB9 with 6 switch inputs
- 3.5 mm stereo jack socket
- Status LED





## **LiNX Drive Input Module**

#### DLX-IN500-A

- Adds full functionality for speciality driving inputs to 400 and 500 level systems
- Built-in Sip'n'Puff input
- DB9 supports proportional and switched input devices
- 12 V 200 mA power supply
- 3.5 mm stereo jack supports powered on/off switch
- Status LED

## **LiNX Output Module**

#### DLX-OUT500-A

- For connecting LiNX system outputs to 3rd party systems or devices
- DB9 with 8 switched outputs
- 3.5 mm stereo jack with 2 switched outputs
- 35 V 100 mA power supply
- Status LED





## **LiNX USB Charger**

#### DLX-USB02-A

- Compact BUS module with 2 x USB charging ports
- Each port supplies 1 amp

NOTE: Available with an optional impact protection shield (DLX-USB02+SH-A)





### **LiNX Third Party Interface**

#### DLX-TPI500-A

- PCB interface to create custom control products that plug directly into the LiNX BUS
- Create proportional or switched drive inputs, or an attendant control unit
- 4 pin BUS connector and multiple connectors for your custom product
- 24 V, 5 V and 3.3 V power supplies (up to 100 mA)



Tools

## **LiNX Access Programming & Diagnostic Tools**

Wireless programming and diagnostic tools for PC and iOS devices are available, featuring live programming, time & date event logs and usage statistics, as well as highly configurable control inputs.

- LiNX Access PC (for Windows-based devices)
- LiNX Access iOS (for Apple devices)
- LiNX Access Keys (DLX-HKEY01-A for Distributors, and DLX-HKEY02-A for Manufacturers)





Cables

DESCRIPTION	PRODUCT CODE
LiNX 0.3 meter bus cable	GLM-BUS030-A
LiNX 0.5 meter bus cable	GLM-BUS050-A
LiNX 0.7 meter bus cable	GLM-BUS070-A
LiNX 1.0 meter bus cable	GLM-BUS100-A
LiNX 1.2 meter bus cable	GLM-BUS120-A
LiNX 1.5 meter bus cable	GLM-BUS150-A
LiNX 1.7 meter bus cable	GLM-BUS170-A
LiNX 2.0 meter bus cable	GLM-BUS200-A
LiNX 2.5 meter bus cable	GLM-BUS250-A
LiNX 4-way bus connector	GLM-CON4W-A
LiNX 0.9 meter extension cable	GLM-EXT090-A
LiNX 0.64 meter extension cable	GLM-EXT064-A
Panel-mount clip for extension cable	GLE80151



#### ACHIEVE AMAZING EVERY DAY.

Being free to move and express yourself is central to the human experience. Dynamic exists to ensure that all people living with restricted mobility enjoy the same freedoms. We partner with innovative customers to bring freedom of movement and expression through high quality medical mobility control and high-tech connectivity.

#### Open new worlds

Mobility solutions powered by Dynamic change millions of lives worldwide every day.

#### Transform your business

Seamless product systems can transform your designs and your business.

#### Empower better outcomes

Clinicians, retailers and clients can interact more effectively to improve outcomes.



Talk to us about how
Dynamic can help
transform your business
and the lives of your
customers.

Dynamic is a company of Allied Motion Technology who jointly develop, manufacture and sell products for the motion control market. These products include brushed and brushless DC motors, brushless servo and torque motors, coreless DC motors, integrated brushless motor drives, gear motors, gearboxes, modular digital servo drives, motion controllers, incremental and absolute optical encoders and related motion control products.

alliedmotion.com

#### **EUROPE**

Ph: +44-1562-826-600 eusales@dynamiccontrols.com

#### **ASIA**

Ph: +886-955-335-243 asiasales@dynamiccontrols.com

#### **AUSTRALASIA**

(CORPORATE OFFICE)
Ph: +64-3-962-2519
sales@dynamiccontrols.com

Dynamic Controls is the world's leading manufacturer of electronic controls for power wheelchairs and scooters.

Actual products may vary from those featured. Not all products may be available at the time of printing.

QMS Certified to ISO 13485

The Bluetooth\* word mark and logos are registered trademarks owned by Bluetooth\* SIG, Inc.



